

TECHNICAL SPECIFICATION: REBARS ALFA 500SD



Description of the product

Weldable, sustainable reinforcing steel featuring improved bonding and high ductility, hot rolled with in-line heat treatment "Tempcore".

Range of dimensions

- Diameter: 8 – 32 mm
- Length: 6 – 18 m

Packaging

- 5 fastenings for bundle length < 9 m:
- 7 fastenings for bundle length 9 to 14 m
- 9 fastenings for bundle length 15 m
- 11 fastenings for bundle length 16 to 18 m

Double-strap fastening with 7 mm diameter wire

Bundle weight:

- 6 m ~ 1400 kg
- 12 m ~ 2300 kg

Labelling

Each bundle is identified with a metal or paper plastic label containing the following information:


- Company logo
- Heat number
- Diameter
- Length
- Weight
- Steel grade
- Production date
- Standards references
- Certification logos
- QR Code

TECHNICAL SPECIFICATION: REBARS ALFA 500SD

Certifications

Each delivery is accompanied by the certificate 3.1 (standard UNI EN 10204)

RIBS GEOMETRY AND ROLLING MARKING



CONFORMITY TO STANDARDS

Country	Standard	Grade	Certifications
GREECE	ELOT 1421-3	B 500 C	✓
ITALY	D.M. 17/01/2018	B 450 C	✓
GERMANY	DIN 488	B 500 B	✓
CROATIA	HRN 1130-2	B 500 B	✓
POLAND	PN-H-93220	B 500 SP	

CHEMICAL COMPOSITION

C % max	P % max	S % max	Cu % max	N % max	Ceq. Max
0.22	0.050	0.050	0.80	0.012	0.50
(0.24)	(0.055)	(0.055)	(0.85)	(0.014)	(0.52)

The figures in brackets refer to product analysis

MECHANICAL PROPERTIES

Standard	Grade	Re N/mm ²	Rm N/mm ²	Rm/Re	Agt %	A5 %	A10 %
ELOT 1421-3	B 500 C	≥ 500		≥ 1.15 ≤ 1.35	≥ 7.5		
D.M. 17/01/2018	B450 C	≥ 450	≥ 540	≥ 1.15 ≤ 1.35	≥ 7.5		
DIN 488	B 500 B	≥ 500		≥ 1.08	≥ 5		
HRN 1130-2	B 500 B	≥ 500		≥ 1.08	≥ 5		
PN-H-93220	B 500 SP	≥ 500		≥ 1.15	≥ 8		

TECHNICAL SPECIFICATION: REBARS ALFA 500SD

				≤ 1.35			
--	--	--	--	-------------	--	--	--

GEOMETRICAL CHARACTERISTICS				
$\varnothing$ mm	8	10	12	≥ 14
Relative rib area fR	≥ 0.040	≥ 0.040	≥ 0.040	≥ 0.056
Relative rib area fR DIN 488	≥ 0.045	≥ 0.052	≥ 0.056	≥ 0.056